



| | | | | | |
|-----|---------------------|----------------------|--------|--------|-------|
| 13 | Name Plate | Stainless Steel | 銘板 | SUS304 | 1 |
| 12 | Gasket | PTFE | ガスケット | PTFE | 1 |
| 11 | Gasket | PTFE | ガスケット | PTFE | 1 |
| 10 | Cap | Brass | キャップ | Brass | 1 |
| 9 | Lock Nut | Brass | ロックナット | Brass | 1 |
| 8 | Adjusting Screw | Brass | 調節ねじ | Brass | 1 |
| 7 | Top Spring Plate | Brass | 上部ばね受 | Brass | 1 |
| 6 | Bottom Spring Plate | Brass | 下部ばね受 | Brass | 1 |
| 5 | Spring | Stainless Steel | 調節ばね | SUS304 | 1 |
| 4 | Spindle | Brass | 弁棒 | Brass | 1 |
| 3 | Valve | Cast Stainless Steel | 弁体 | SCS14A | 1 |
| 2 | Valve Seat | Cast Stainless Steel | 弁座 | SCS14A | 1 |
| 1 | Spring Case | Bronze | ばね箱 | CAC406 | 1 |
| No. | Name of Parts | Material | 部品名 | 材質 | Q. TY |

| Size | d | D | L | H ₁ | H | Weight (kg) |
|------|----------|----|----|----------------|-------|-------------|
| 15A | Rc 1/2 | 16 | 34 | 40 | 128 | 0.7 |
| 20A | Rc 3/4 | 21 | 38 | 43 | 128.5 | 0.8 |
| 25A | Rc 1 | 26 | 43 | 51.5 | 144.5 | 1.1 |
| 32A | Rc 1 1/4 | 33 | 50 | 61.5 | 181.5 | 1.8 |
| 40A | Rc 1 1/2 | 41 | 60 | 60 | 205 | 2.8 |
| 50A | Rc 2 | 51 | 75 | 76 | 245.5 | 4.7 |

| Specification | |
|---------------|-----|
| Fluid | |
| Set Press. | MPa |
| Temp. | ℃ |
| Flow Rate | |

TYPE AL-150 SAFETY RELIEF VALVE

安全リリーフ弁

| | |
|-------------|---------------|
| Approval | T. Watanabe |
| Check | T. Mori |
| Drawing | T. Nagasaka |
| Drawing No. | Y-983-1901-1C |
| Date | 24 JUN. 2021 |

