



(mm)

Size	L	H ₁	Screen		d	Flange JIS 30K RF						⑦ Plug
			ds	ls		D	t	f	g	C	n-h	
15A	180	100	24	70	15	115	18	1	55	80	4-19	R 1/2
20A	180	100	24	70	20	120	18	1	60	85	4-19	R 1/2
25A	200	113	33	80	25	130	20	1	70	95	4-19	R 1/2
32A	240	140	46	100	32	140	22	2	80	105	4-19	R 1/2
40A	240	140	46	100	40	160	22	2	90	120	4-23	R 1/2
50A	275	170	56	120	50	165	22.5	2	105	130	8-19	R 1/2
65A	310	188	73	125	65	200	26	2	130	160	8-23	R 1/2
80A	345	215	88	145	80	210	29	2	140	170	8-23	R 1/2
100A	395	275	108	200	100	240	32	2	160	195	8-25	R 1/2
125A	470	325	138	230	125	275	36	2	195	230	8-25	R 3/4
150A	520	380	158	280	150	325	38	2	235	275	12-27	R 3/4
200A	655	475	208	350	200	370	42	2	280	320	12-27	R 3/4
250A	780	580	270	450	250	450	48	2	345	390	12-33	R 1

※No. 7のプラグは仕様により無しとなる場合があります。

No.	Name of Parts	Material	部品名	材質	Q. TY
8	Name Plate	Stainless Steel	銘板	SUS304	1
7	Plug	Carbon Steel	プラグ	S25C	1
6	Nut	Carbon Steel	ナット	S45C	1set
5	Stud Bolts	Carbon Steel	植込みボルト	S45C	1set
4	Gasket	Non-Asbestos	ガスケット	Non-Asbestos	1
3	Screen	Stainless Steel	スクリーン	SUS304	1
2	Cover	Carbon Steel	ふた	S25C	1
1	Body	Cast Steel	本体	SCPH2	1

Specification	
Fluid	
Press.	MPa
Temp.	℃
Flow Rate	
Inside Screen	Mesh
Outside Screen	∅ - ㏍/cm ²

TYPE SY-10-30 STRAINER
ストレーナ

Approval	H. Kimura
Check	M. Murata
Drawing	T. Nagasaka
Drawing No.	Y-199-2622-2B
Date	3 MAR. 2021

