



Model (型式)	Orifice Size (オリフィスサイズ)	Max. Differential Press. (最高作動圧力差)
TB-813- 1.0	1/2 (12.7mm)	0.10 MPa
TB-813- 2.1	3/8 (9.5mm)	0.21 MPa
TB-813- 4.2	5/16 (7.9mm)	0.42 MPa
TB-813- 5.6	9/32 (7.1mm)	0.56 MPa
TB-813- 8.7	1/4 (6.4mm)	0.87 MPa
TB-813-12.6	7/32 (5.6mm)	1.26 MPa
TB-813- 16	3/16 (4.8mm)	1.60 MPa

No	Name of Parts	Material	部品名	材質	Q. TY
13	Name Plate	Stainless Steel	銘板	SUS304	1
12	Plug	Carbon Steel	プラグ	AISI1008-1010	1
11	Bolts & Nuts	Carbon Steel	ボルト・ナット	ASTM B633 TYPE1	1set
10	Guide Pipe	Stainless Steel	パイプノック	SUS304	1
9	Gasket	Non Asbestos	ガスケット	G#3400	1
8	Plug	Carbon Steel	プラグ	AISI1008-1010	1
7	Pipe	Carbon Steel Pipe	入口案内管	ASTM A53	1
6	Lever	Stainless Steel	レバー	ASTM A240 304	1
5	Buket	Stainless Steel	バケット	ASTM A240 304	1
4	Valve Seat	Stainless Steel	弁座	ASTM A582 440F	1
3	Valve	Stainless Steel	弁体	ASTM A582 440F	1
2	Cover	Cast Iron	ふた	ASTM A48 Class 30	1
1	Body	Cast Iron	本体	ASTM A48 Class 30	1

(mm)

Size	d	L	H	H1	A	Plug No.8	Plug No.12	Weight (kg)
20A	Rc 3/4	197	299	179	178	NPT3/4	NPT1/2	12.5
25A	Rc 1	197	299	179	178	NPT3/4	NPT1/2	12.5

Specification	
Fluid	
Press.	MPa
Temp.	℃

TYPE TB-813 STEAM TRAP
スチームトラップ

Approval	M. Kume
Check	Y. Aoyama
Drawing	S. Kanematsu
Drawing No.	Y-354-0801-2B
Date	9 DEC.2011

